



¿Mejor?... Imposible.



MirageMEXICO

mirage.mx

 **mirage**



# ABSOLUT X



ESPECIFICACIONES		12k-115	12k-220	18k-220	24k-220
VOLTAJE DE OPERACIÓN	Ph / V~ /Hz	1/ 115/ 60	1/ 230/ 60	1/ 230/ 60	1/ 230/ 60
CAPACIDAD DE ENFRIAMIENTO	BTU/h	12,000	12,000	18,000	26,000
	W(i)	3,500	3,500	5,280	7,620
CONSUMO PROMEDIO	W	950	1,000	1,600	2,000
CORRIENTE PROMEDIO	A	8.5	4.5	7.7	9.6
CAPACIDAD DE CALEFACCIÓN	BTU/h	12,500	12,500	19,000	26,000
	W(i)	3,665	3,665	5,570	7,620
CONSUMO PROMEDIO	W	910	9,80	1,510	1,980
CORRIENTE PROMEDIO	A	8.5	4.5	7.7	9.6
CIRCULACIÓN DE AIRE	m <sup>3</sup> /h	550	550	850	950
REMOSION DE HUMEDAD	l/h	1.20	1.20	1.70	1.80
NIVEL DE RUIDO					
EVAPORADOR	dB(A)	33	33	35	37
CONDENSADOR	dB(A)	52	52	56	56
TIPO DE COMPRESOR		MIRAGE TURBO INFINITY / Fixed speed Rotary			
MOTOR VENTILADOR					
INTERIOR Velocidad	H/M/L/ (rpm)	1350/1250/1100/950	1350/1250/1100/950	1350/1200/1050/900	1350/1150/1000/850
CAPACITOR	(μF)	4	1	1.5	2.5
EXTERIOR Velocidad	(rpm)	850	850	915	815
CAPACITOR	(μF)	7	2	2.5	3.5
ABANICO					
TURBINA DIAMETRO/LONGITUD	(mm)	Φ85x596	Φ85x596	φ98x710	Φ98x765
DIÁMETRO ASPA	(mm)	400	400	400	460
DIMENSIONES					
EVAPORADORA (AnxAlxProf)	(mm)	790x265x177	790x265x177	940x298x200	1007x315x219
C/EMPAQUE (AnxAlxProf)	(mm)	873x251x370	873x251x370	1013x383x300	1076x398x328
CONDENSADORA (AnxAlxProf)	(mm)	776x540x320	776x540x320	848x540x320	913x680x378
C/EMPAQUE (AnxAlxProf)	(mm)	823x595x358	823x595x358	881x595x363	997x740x431
PESO BRUTO (indoor / outdoor)	(kg)	12/35	12/35	17/44	20/55
CARGA DE REFRIGERANTE	(kg)	R22/0.62/0.78	R22/0.55/0.60	R22/1.0/1.24	R22/1.20/1.35
CARGA ADICIONAL	(g/m)	15/20	15/20	15/20	15/20
DIAMETRO DE TUBERÍA	(Pulg)	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4	5/8 - 1/4

